

## LIEBHERR





2.4" Touchscreen Display: The high-resolution, highcontrast 2.4" touchscreen display is located behind the door and can be read from any angle. The stored menu options are Intuitive and easy-to-operate.



BioFresh-Plus: With the adjustable temperature range of 0°C and -2°C, BioFresh-Plus technology offers even more flexibility for your produce. The BioFresh-Plus drawer includes a versatile Fish & Seafood-Safe.




PowerCooling: A high-performance system that allows freshly stored items to be chilled rapidly while maintaining an even temperature throughout the interior. In this energyefficient BluPerformance range, the fan switches off when the appliance door is opened, saving valuable energy.


Premium quality characterises the SBSes 8683 from our BluPerformance series. Highquality components and materials, perfect workmanship, and precise touch electronics and digital temperature display make this side-by-side fridge-freezer an energy efficient household appliance.

Fruits, vegetables, fish, meat, and dairy products remain fresher for much longer thanks to BioFresh technology. Our NoFrost technology means that the appliance never has to be defrosted. An elegant and classic design with a SmartSteel surface ensures that the SBSes 8683 will remain a household highlight for years to come.

*Side-by-Sides comprised of two models	SGNPes 4365	SKBes 4360
Energy consumption (kWh/yr) I Star rating	199   5.0	130   5.5
Compressors	1	1
Total Usable Litres	277	372
Refrigerator Usable Litres	-	236
Freezer Usable Litres	277	-
BioFresh Usable Litres	-	136
Control system and display I Child proof	2.4"Touch display I Yes	2.4"Touch display   Yes
PremiumPlus   LED : lighting	- I Yes	Yes I -
Sabbath mode	Yes	Yes
SoftSystem hinge - assists closure	Yes	Yes
Door open I Temperature : alarms	Yes I Yes	Yes I -
BioFreshPlus drawers on telescopic rails	-	1
BioFresh drawers on telescopic rails	-	2
SuperCool   VarioSafe	-   -	Yes I Yes
SuperFrost   VarioSpace	Yes I Yes	- -
Integrated bottle shelf	-	Yes
Freezer drawers I Ice cube drawer	8 1	-1-
IceMaker   Ice cube capacity (kg/24h)	Yes   0.8	-   -
Stainless steel hose supplied (m)	1.5	-
Stainless steel with SmartSteel Doors   Walls	Yes I Yes	Yes I Yes
Default hinge	Left	Right
Voltage (V)   Rated Current (A)	220 - 240   1.3	220 - 240   1.2
Made in	Germany	Germany



wall spacers provided with the appliance must be used. This increases the appliance depth by approximately 1.5 cm. If the wall spacers are not used, the appliance will remain fully functional, but will have a slightly higher energy



b = 700 mmc = 110 mm

Plumbing must be installed adjacent to the side of the appliance which contains the IceMaker

Water pressure must be between 0.15 MPa and 0.6 MPa (1.5 bar - 6 bar)

Important information: For Side-by-Side installation the freezer or the appliance with freezer compartment must be

installed on the left as viewed from the front to prevent possible formation of condensation.

Note: Whilst every effort is made to ensure all specifications and information in this flyer are accurate, Liebherr reserves the right to make changes without notification. Where actual appliance measurements, specifications, and ratings are crucial, we recommend that the actual appliance installation instructions that accompany each appliance be checked. Liebherr will not be liable for any loss.