

LIEBHERR

Contents

001		
1 1.1 1.2 1.3 1.4 1.5 1.6 1.7	Appliance at a glance Scope of delivery Overview of the appliance and its equipment SmartDevice Appliance range of use Conformity SVHC substances according to REACH regulation. EPREL database	3 3 3 3 4 4 4 4
2	General safety instructions	4
3 3.1 3.2	Putting into operation Switching on appliance Inserting the components	6 6
4 4.1 4.2	Foods management Storing food Storage times	6 6 7
5	Saving energy	7
6 6.1 6.1.1 6.1.2	Controls Controls and displays Status display Navigation	
6.1.3	Display symbols	
6.2	Control concept	8
6.2.1 6.2.2	Activating/deactivating the function Selecting function value	
6.2.3	Activating/deactivating settings	9
6.2.4	Selecting the setting value	9
6.2.5	Go to the Customer menu	
6.3	Functions Turn off appliance	
()		10
•)) (((•	WiFi	. 10
5 °c	Temperature	10
D1	D-Value	11
*	SuperCool	11
(\mathcal{L})	PowerCool	11
**	SuperFrost	11
	PartyMode	11
	HolidayMode	
$\underline{\mathbb{W}}$	SabbathMode	
\square	EnergySaver	
	IceMaker / MaxIce*	
5 Recuberitie	Ice cubes*	
Ś	TubeClean*	
$\langle O \rangle$	CleaningMode	14

	Display brightness	.14
	Door alarm	14
×ſm	Entry lock	14
Ň	Language	14
Service No: Model Index: Serail#:	Info	15
Σ	Reminder	. 15
\int	Reset	. 15
6.4 6.4.1 6.4.2 6.4.3	Fault messages Warnings Message DemoMode	. 15
7 7.1 7.2 7.3 7.4 7.5 7.6 7.7 7.8 7.9 7.10 7.11 7.12	Features	16 16 17 17 17 18 18 20 20 20 20 21 21 21
8 8.1 8.2 8.3 8.4	Maintenance FreshAir carbon filter Disassembling / assembling pull-out systems Defrosting the appliance Cleaning the appliance	23 23 23 24 24
9 9.1 9.2 9.3 9.4 9.5	Customer help Technical specifications Operating noises Technical fault Customer Services Model plate	25 26 26 27 28
10	Shutting down	28
11 11.1 11.2	Disposal Preparing appliance for disposal Disposing of the appliance in an environmentally friendly manner	28 28 28

The manufacturer is continually working on the further development of all types and models. Please be aware that we reserve the right to make changes to the shape, equip-ment and technology.

Symbol	Explanation
	Read instructions
	Please read the information in these instruc- tions carefully to understand all of the benefits of your new appliance.

Symbol	Explanation		the appliance and its
	Full instructions on the internet	equipment	
	You can find detailed instructions on the internet using the QR code on the front of these instruction or by entering the service number at home.liebherr.com/fridge-manuals. The service number can be found on the serial tag:		
	<i>Fig.</i> Example illustration Check appliance Check all parts for transport damage. If you have any complaints, please contact your agent or customer service.	B	
*	Differences These instructions apply to a range of models, so differences are possible. Sections that apply to certain models only are marked with an asterisk (*).	©-	
\land	Instructions and results Instructions are marked with a ▶. Results are marked with a ▷.		
	Videos Videos about the appliances are available on the YouTube channels of Liebherr-Hausgeräte.	یا Fig. 1 Example illustratior Tem (A) Fridge section	perature range (C) Freezer compartmen
his User G ICNd(i) 5 ICNd(i) 5 SICNd 51	173	 (B) EasyFresh (D) Coldest zone (1) Controls (2) Fan with FreshAir 	Features (10) EasyFresh-Safe (11) Freezer compartmen
lote f your appl	iance has an N in its appliance designation, it is	active carbon filter (3) Dry rear wall	(12) IceMaker*

If your appliance has an N in its appliance designation, it is a NoFrost appliance.

1 Appliance at a glance

1.1 Scope of delivery

Check all parts for damage during transport. If you have any complaints, please contact your retailer or Customer Services (see 9.4 Customer Services).

Your new appliance comes with the following parts:

- Built-in appliance
- Features (depending on the model)
- Installation materials (depending on the model)
- "Quick Start Guide"
- "Installation Guide"
- Service Brochure

Note

(4) Split shelf

(6) VarioSafe

(7) Space for baking tray

(9) Drainage outlet

(8) Lid for EasyFresh-Safe

(5) Shelf

Shelves, drawers and baskets are arranged for optimum energy efficiency when the appliance is delivered. Changing how the shelves, for example, are inserted in the fridge compartment does not have any impact on energy consumption.

(13) VarioSpace

(15) Nameplate

(17) Bottle rack

(18) VarioBoxes

(16) Door rack

(14) Freezer tray*

1.3 SmartDevice

SmartDevice is the networking solution for your fridge-freezer.

If your appliance SmartDevice-enabled or compatible, you can quickly and easily connect your appliance to your WiFi. With the SmartDevice app, you can operate your appliance from a mobile device. Additional functions and setting options are available in the SmartDevice SmartDevice app. SmartDeviceenabled ance:*

SmartDeviceance.*

Your appliance is equipped with a appli- SmartDeviceBox. In order to connect your appliance to the WiFi, you need to download the SmartDevice app.*

Your appliance is compatible for use compatible appli- with the SmartDeviceBox. You must first purchase and install the Smart-DeviceBox. In order to connect your appliance to the WiFi, you need to download the SmartDevice app.*



information smartdevice.liebherr.com More about SmartDevice:

the home.liebherr.com/shop/de/deu/ Purchasing SmartDeviceBox in the Liebherr-Hausgeräte store:*

Downloading the SmartDevice app:



smartdevicebox.html*

After installing and configuring the SmartDevice, you can connect your appliance to the WiFi using the SmartDevice app and the WiFi appliance function (see WiFi).

Note

You cannot use the SmartDeviceBox in the following countries: Belarus, Kazakhstan, Russia. The SmartDevice function is not available.

1.4 Appliance range of use

Intended use

The appliance is only suitable for cooling food products in a domestic or household-like environment. This includes, for example, use:

- in staff kitchens, bed and breakfast establishments.
- by guests in country houses, hotels, motels and other accommodation,
- for catering and similar services in the wholesale trade.

All other types of use are not permitted.

Foreseeable misuse

The following applications are expressly forbidden:

- Storing and refrigerating medicines, blood plasma, laboratory preparations or similar substances and products based on the Medical Device Directive 2007/47/EC
- Use in areas at risk of explosions

Misusing the appliance may lead to damage to the goods stored or they may spoil.

Climate classifications

Depending on the climate classification the appliance is designed to operate in restricted ambient temperatures. The climate classification applying to your appliance is printed on the rating plate.

Note

Keep to the specified ambient temperatures in order to guarantee that the appliance works properly.

Climate clas- sification	for ambient temperatures of
SN	10 °C to 32 °C
N	16 °C to 32 °C
ST	16 °C to 38 °C
Т	16 °C to 43 °C
SN-ST	10 °C to 38 °C
SN-T	10 °C to 43 °C

1.5 Conformity

The refrigerant circuit has been tested for leaks. When installed, the appliance complies with the applicable safety regulations and with the corresponding directives.

For market	the t:*	EU	The appliance complies with directive 2014/53/EU.*
For market		GΒ	The appliance complies with Radio Equipment Regulations 2017 SI 2017 No. 1206.*

The full text of the EU Declaration of Conformity is available on the following website: www.Liebherr.com

1.6 SVHC substances according to **REACH** regulation

You can check whether your appliance contains SVHC substances according to REACH regulation at the following link: home.liebherr.com/de/deu/de/liebherr-erleben/nachhaltigkeit/umwelt/scip/scip.html

1.7 EPREL database

Details about energy labelling and ecodesign requirements will be available on the European product database (EPREL) from 1st March 2021. You can access the product database at the following link: https://eprel.ec.europa.eu/ You will be asked to enter the model ID. You can find the model ID on the nameplate.

2 General safety instructions

Please keep these operating instructions in a safe place so you can refer back to them at any time.

If you pass the appliance on, please hand these operating instructions to the next user.

Read these operating instructions carefully before use to ensure safe and correct use of the appliance. Follow the instructions, safety instructions and warning messages included at all times. They are important for ensuring you can operate and install the appliance safely and without any problems.

Danger for the user:

- This device can be used by children and people with impaired physical, sensory or mental abilities or with a lack of experience and knowledge provided that they are supervised or have received instruction in the safe use of this device, and about the resulting hazards. Children must not play with this appliance. Cleaning and user maintenance work must not be carried out by children without adult supervision. Children aged between 3 and 8 are allowed to load and unload the appliance. Children below the age of 3 must be kept away from the appliance unless they are under continuous adult supervision.
- The socket must be easily accessible so that the appliance can be disconnected quickly from the electricity in an emergency. It must not be located in the area behind the appliance.
- When disconnecting the appliance from the supply, always take hold of the plug. Do not pull the cable.
- In the event of a fault pull out the mains plug or deactivate the fuse.
- Do not damage the mains power cable. Do not operate the appliance with a defective mains power cable.
- Only customer service or other specially trained staff may repair or perform other operations on the appliance.
- Only install, connect and dispose of the appliance according to the instructions.
- Only use the appliance when is installed.
- The manufacturer is not liable for damage caused by a faulty fixed water connection.

Fire hazard:

- The coolant used (information on the model plate) is ecofriendly but also flammable. Any leaking coolant may ignite.
 - Do not damage the refrigerant circuit pipes.
 - Do not handle ignition sources inside the appliance.

- Do not use electrical appliances inside the appliance (e.g. steam cleaners, heaters, ice cream makers, etc.).
- If the refrigerant leaks: remove any naked flames or ignition sources from the vicinity of the leakage point. Properly air the room. Inform customer services.
- Do not store explosives or sprays using combustible propellants such as butane, propane, pentane, etc. in the appliance. To identify these spray cans, look for the list of contents printed on the can, or a flame symbol. Gases possibly escaping may ignite due to electrical components.
- Keep burning candles, lamps and other items with naked flames away from the appliance so that they do not set the appliance on fire.
- Please be sure to store alcoholic drinks or other packaging containing alcohol in tightly closed containers. Any alcohol that leaks out may be ignited by electrical components.

Danger of tipping and falling:

- Do not misuse the plinth, drawers, doors etc. as a step or for support. This applies particularly to children.

Danger of food poisoning:

- Do not consume food which has been stored too long.

Danger of frostbite, numbness and pain:

 Avoid prolonged skin contact with cold surfaces or refrigerated/frozen goods or take protective measures, e.g wear gloves.

Danger of injury and damage:

- Hot steam can lead to injury. Do not use electrical heating or steam cleaning equipment, open flames or defrosting sprays to defrost.
- Do not use sharp implements to remove the ice.

Risk of crushing:

Do not hold the hinge when opening and closing the door. Fingers may get caught.

Symbols on the appliance:



This symbol may be located on the compressor. It relates to the oil in the compressor and makes reference to the risk that: Swallowing or inhaling can be fatal. This advice is only relevant to recycling. There is no danger in normal operation.

Putting into operation



This symbol is located on the compressor and indicates the danger of flammable materials. Do not remove the sticker.

This or a similar sticker may be located on the rear of the appliance. This sticker indicates that there are vacuum insulation panels (VIP) or perlite panels in the door and/or housing. This advice is only relevant to recycling. Do not remove the sticker.

Please note the warning messages and other specific advice in the other chapters:

	DANGER	indicates an immediately hazardous situation which will lead to death or serious injuries if it is not avoided.
\triangle	WARNING	indicates a hazardous situation which may lead to death or serious injuries if it is not avoided.
\triangle	CAUTION	indicates a hazardous situation which may lead to minor or moderate injuries if it is not avoided.
	NOTICE	indicates a hazardous situation which may lead to damage to property if it is not avoided.
	Note	indicates useful instructions and tips.

3 Putting into operation

3.1 Switching on appliance

Ensure that the following conditions are met:

- Appliance is installed and connected according to installation instructions.
- □ All adhesive strips, adhesive and protective films as well as transport safety devices in and on the appliance are removed.
- □ All marketing leaflets are removed from the drawers.




Fig. 2

Switch on the appliance using the display.




Fig. 3

Select the language.

 \triangleright The status display appears.

The appliance starts in DemoMode:

If the appliance starts in DemoMode, you can deactivate DemoMode within the next 5 minutes.





- Press DemoMode for 3 seconds.
- ▷ DemoMode is deactivated.

Note

The manufacturer recommends:

- Place the food inside: Wait for around 6 hours until the set temperature is reached.
- **Store frozen foods** at -18 °C or colder.

3.2 Inserting the components

Note

Accessories can be purchased from the Liebherr-Hausgeräte store at home.liebherr.com/shop/de/deu/ zubehor.html.

Insert the supplied components to make the most of your appliance.

4 Foods management

4.1 Storing food



Do not use any electrical appliances in the food area of the appliance unless recommended by the manufacturer.

Note

The energy consumption increases and the cooling power goes down if ventilation is not sufficient.

Always keep air slots clear.

When storing food, always observe the following:

- $\hfill\square$ Air vents on the inside rear wall are unobstructed.
- Air vents on the fan are unobstructed.
- □ Food is in sealed packaging.
- □ Foods that easily absorb or give off smell or taste are stored in sealed containers or covered.
- Raw meat and fish are in clean, sealed containers to prevent them coming into contact with or dripping onto other foods.
- Liquids are in sealed containers.
- Foods are not stored too closely together, as the air needs to circulate.

Note

Failure to follow these guidelines can lead to food perishing.

4.1.1 Fridge section

The natural air circulation creates a range of temperatures.

Arrange your food as follows:

- In the top section and in the door: butter and cheese, preserves and tubes.
- ▶ In the coldest zone *Fig. 1 (D)*: Perishable foods such as ready-to-eat meals, meat and sausages
- On the bottom shelf: Raw meat and fish

4.1.2 EasyFresh-Safe 🛈 🥖 🚳

This compartment is great for non-packaged foods, such as fruit and vegetables.

The air moisture in the compartment depends on the moisture content of the items being stored and the number of times the door is opened. You can adjust the air moisture.

Arrange your food as follows:

- Store your loose fruit and vegetables.
- ► Excessive air moisture: Regulate the air humidity (see 7.8 Adjusting the moisture levels).

4.1.3 Freezer compartment

This provides a dry, frosty storage climate at -18 °C. A frosty climate is great for storing frozen food and frozen goods for several months, making ice cubes and freezing fresh food.

Freezing food

You can freeze as many kilograms of fresh food within 24 hours as indicated on the nameplate (see 9.5 Model plate) under "freezing capacity ... kg/24h".

So that the food is rapidly frozen through to the core, keep to the following quantities per pack:

- Fruit, vegetables up to 1 kg
- Meat up to 2.5 kg

Before freezing goods, please make sure of the following:

- □ SuperFrost is activated (see 6.3 Functions) when the amount of food to freeze exceeds approx. 2 kg.
- With a small amount of frozen goods: SuperFrost is activated approx. 6 hours prior.
- With the maximum amount of frozen goods: SuperFrost is activated approx. 24 hours prior.

Arrange your food as follows:

Risk of injury from glass fragments!

Drink bottles and cans may explode if frozen. This applies particularly to carbonated drinks.

Do not freeze bottles and cans of drink!

With a small amount of frozen goods:

- Distribute packaged groceries across all drawers.
- If possible, place groceries at the back of the drawer near the rear wall.
 - With a maximum amount of frozen goods:
- Distribute packaged groceries across all drawers.
- If possible, place groceries at the back of the drawer near the rear wall.
- With a maximum amount of frozen goods:
 Once SuperFrost deactivates automatically, place food
- into the drawer.

Defrost the food

- In the fridge
- In the microwave
- In the stove/oven
- At room temperature

Risk of food poisoning!

Do not re-freeze thawed food.

- Only take out the food you need at the time.
- Cook defrosted food as soon as possible.

Freezer tray*

Use the freezer tray for berries, herbs, vegetables and other small goods without them freezing together in the process. The food keeps its shape and is easier to separate into portions later on.

You can also store the freezer packs in the freezer tray to save space.

Spread food, unsealed, at a good distance apart, over the whole surface of the freezer tray.

4.2 Storage times

Refer to the specified storage times as a guide.

In the case of foods with a minimum shelf life, the date indicated on the packaging still applies.

4.2.1 Fridge section

Always follow the best-before date stated on the packaging.

4.2.2 Freezer compartment

Recommended storage period for various types of food		
Ice cream	at -18 °C	2 to 6 months
Sausages, ham	at -18 °C	2 to 3 months
Bread, baked goods	at -18 °C	2 to 6 months
Game, pork	at -18 °C	6 to 9 months
Fatty fish	at -18 °C	2 to 6 months
Lean fish	at -18 °C	6 to 8 months
Cheese	at -18 °C	2 to 6 months
Poultry, beef	at -18 °C	6 to 12 months
Vegetables, fruit	at -18 °C	6 to 12 months

5 Saving energy

- Pay attention to good ventilation. Do not cover ventilation holes or grids.
- Always keep the fan air slits clear.
- Do not install the appliance in direct sunlight, next to an oven, radiator or similar.

- Energy consumption depends on the installation conditions, e.g. the ambient temperature (see 1.4 Appliance range of use) . A warmer ambient temperature can increase the energy consumption.
- Open the appliance for as short a time as possible.
- The lower the temperature is set the higher the energy consumption.
- Sort your food: home.liebherr.com/food.
- Keep all food properly packed and covered. This prevents frost from forming.
- Only take food out for as long as necessary so that it doesn't warm up too much.
- Inserting warm food: allow to cool down to room temperature first.
- Thaw frozen food in the refrigerator.
- For longer periods of absence, use HolidayMode (see HolidayMode).

6 Controls

6.1 Controls and displays

The display gives you a quick overview of the temperature setting and the status of functions and settings. Select or adjust functions by activating/deactivating or selecting a value.

6.1.1 Status display




Fig. 5

- (1) Temperature display of (2) the fridge section
 - (2) Freezer compartment temperature display

The Status display shows the set temperatures and is the home display. From there, you can navigate to the options and settings.

6.1.2 Navigation

Navigate in the menu to access the individual functions. An audible signal sounds after confirming a function or setting. If no selection is made after 10 seconds, the display switches to the Status display.

Navigation Description	
	Press briefly Activate/deactivate function. Confirm selection. Open submenu.
Bor (Bo	Long press (3 seconds) Activate/deactivate function. Increasing/decreasing bar appears in the display. Confirm selection. Reset appliance/values. Switch appliance on/off.

Navigation	Description
*5 }	Swipe Navigate in the menu. Search for values.
	Briefly press "Back" symbol Display goes back one level.
No action for 10 seconds	Display switches to the Status display.

6.1.3 Display symbols

Display symbols provide information on the current appliance status:

Symbol



Appliance status

Standby

The appliance or temperature zone is switched off.



Flashing number

Appliance is working. Temperature flashes until the set temperature is reached.



Flashing symbol

Appliance is working. Setting is made.

6.2 Control concept

6.2.1 Activating/deactivating the function

You can activate/deactivate the following functions:

Symbol	Function
*	SuperCool ^x
Ś	PowerCool×
***	SuperFrost ^x
	IceMaker and MaxIce ^{x*}
	PartyMode ^x
	HolidayMode

Symbol

Function



EnergySaver

^x When function is on, the appliance works harder. This means appliance noise when operating may be louder for a short while, and more energy will be consumed.

- Swipe left in the display until the function appears.
- Confirm selected function with a short tap.
- \triangleright You hear the confirmation tone.
- \triangleright Status appears in the menu.
- \triangleright Function is on/off.

6.2.2 Selecting function value

With the following functions you can set a value in the submenu:

Symbol	Function
5 c	Cool: Setting the temperature Turn on/off the temperature zone
-18 _{°C}	Freeze: Setting the temperature Switch the appliance on/off

Swipe left in the display until the function appears.

- Confirm selected function with a short tap.
- Select the setting value by swiping the display.
- Press briefly to confirm the selected value.

6.2.3 Activating/deactivating settings

You can activate/deactivate the following settings:

	, · · · · · · · · · · · · · · · · · · ·
Symbol	Setting
•))	WiFi ¹
×Im	Entry lock ²
	SabbathMode ²
$\langle O \rangle$	Cleaning Mode ²
۲ <u>۲</u> ۲	Reminders ¹
\bigcirc	Reset ²
(Switch off ²
Swine left in	the display until Settings 🖉 appears

- Swipe left in the display until Settings 🖾 appears.
- Tap to confirm settings.
- Swipe until you see the setting you want.

¹ Activate setting (shortpress)

- Tap briefly to confirm.
- \triangleright You hear the confirmation tone.
- \triangleright Status appears in the menu.
- \triangleright Setting is on / off.

² Activate setting (longpress)

- Press the selection for 3 seconds to confirm.
- \triangleright You hear the confirmation tone.

- \triangleright Status appears in the menu.
- ▷ Display changes.

6.2.4 Selecting the setting value

With the following settings you can set a value in the submenu:

Symbol	Settings	
$- \sum_{l=1}^{l} \sum_{i=1}^{l}$	Brightness	
	Door alarm	
	Language	

- Swipe left in the display until Settings @ appears.
- ▶ Tap to confirm settings.
- Swipe until you see the setting you want.
- ► Tap briefly to confirm.
- Select the desired setting value by swiping the display.
- ► Tap briefly to confirm.
- > You hear the confirmation tone.
- \triangleright Status appears briefly in the submenu.
- \triangleright Display switches back to the menu.

6.2.5 Go to the Customer menu

You can see the following settings in the Customer menu:

Symbol	Function	
D1	D-Value ¹	
*	TubeClean ^{2*}	
5	Ice cubes ^{1*}	
34044/Kose 103 19 50 000000 19 30 19 30 19 20 TCC /A 80 Software	Software	
 Swipe left in the display until the settings appear. Tan settings 		

- Tap settings.
- \triangleright The submenu appears.
- Swipe left in the display until the appliance information
 appears.
- Press for 3 seconds.
- \triangleright The input menu for a numerical code appears.
- Enter the numerical code 151.
- \triangleright The customer menu appears.
- Swipe left in the display until the desired setting appears.

$^{\rm 1}$ Select the value

- Confirm with a short tap.
- You hear the confirmation tone.
- \triangleright Status appears briefly in the display.
- \triangleright Display switches back to the menu.

² Activate the setting


- ▶ To confirm, press the display for 3 seconds.
- \triangleright You hear the confirmation tone.
- \triangleright Status appears on the display.
- Dash The symbol flashes as long as the appliance is working.

6.3 Functions

Turn off appliance

This setting turns off the whole appliance.

Switching off the entire appliance



- Fig. 6
- Turning off the IceMaker .*
- Activating/deactivating (see 6.2 Control concept).
- \triangleright Off: Display goes black.

WiFi

Use this function to connect your appliance to the WiFi. You can then operate it via the SmartDevice app on a mobile device. You can also use this function to disconnect or reset the WiFi connection. To connect your appliance to the WiFi, you need the SmartDeviceBox. For more information about the SmartDeviceBox and how to use the SmartDevice app: (see 1.3 SmartDevice)

Note

You cannot use the SmartDeviceBox in the following countries: Belarus, Kazakhstan, Russia. The SmartDevice function is not available.

Establishing a WiFi connection

Make sure that the following requirements are fulfilled:

- □ You have purchased and inserted a SmartDeviceBox. (see 1.3 SmartDevice) *
- □ You have installed the SmartDevice app (see apps.home.liebherr.com).




Fig. 7

- Activate the setting. (see 6.2 Control concept)
- ▷ Connection is established: Connecting appears. The symbol flashes.
- \triangleright Connection is established: WiFi appears, the display turns blue.
- ▷ Connection failed: WiFi Error appears.

Disconnecting from the WiFi

Deactivate the setting. (see 6.2 Control concept)






Fig. 9

 \triangleright

 \triangleright The connection and other settings are reset to the factory settings.

5 Temperature

The temperature depends on the following factors:

The amount of times the door is opened

Freezer compart- -18 °C

- How long the door is open for _
- The room temperature of the installation site
- The type, temperature and amount of food

Temperature zone	Recommended setting	
5 ° Fridge section	5 °C	

Setting the temperature in the fridge compartment




Fig. 10 Complete the steps.

 \triangleright Temperature is set.

Setting the temperature in the freezer compartment




Fig. 11

- Complete the steps.
- ▷ Temperature is set.

Switching off a temperature zone

You can switch off the fridge compartment separately.

If you switch off the freezer compartment, all temperature zones are switched off.

- Deactivate IceMaker. *
- ► Set the value. (see 6.2 Control concept) .
- \triangleright



D-Value

Note

Liebherr recommends:

Operate the appliance with dry rear panel to avoid visible condensation and goods freezing to the rear panel or each other.

The D-Value specifies whether you are operating your fridge compartment with or without a dry rear panel. The rear panel is mounted in the appliance in its delivery condition. The default setting for the D-Value is D1.

remove the You can rear panel for cleaning. (see 8.4.3 Cleaning the dry rear panel) To operate the appliance without a rear panel, you need to set the D-Value to D2.

Choose the setting

▶ Set the value in the customer menu. (see 6.2 Control concept)



This function selects the lowest cooling temperature. This gives you colder storage temperatures.

This function is relevant to the fridge section Fig. 1 (A)

Use:

- Cool large amounts of food quickly.

Activating/deactivating the function

▶ Using the fridge section: activate the function when you add the goods.

- Activating/deactivating (see 6.2 Control concept). -or-
- Activate/deactivate using the SmartDevice app.*

The function automatically turns off. The appliance goes back to normal mode. The temperature adjusts itself to the set level.



PowerCool

This function provides the perfect blanket temperature to cool your food.

This function refers to the fridge section Fig. 1 (A).

Use:

- At higher room temperatures (from approx. 35 °C) -
- When humidity is high e.g. on summer days _
- When storing moist goods, to avoid condensation building up inside

Activating/deactivating the function

Activating/deactivating (see 6.2 Control concept).

Note

The fan can run even when function is deactivated. This ensures optimal temperature distribution in the appliance.

 \triangleright Function activated: Energy consumption of the appliance is slightly increased.

SuperFrost

This function selects the lowest freezing temperature. This gives you colder storage temperatures.

This function refers to the freezer section Fig. 1 (C).

Use:

- For storing more than 2 kg fresh food every day.
- Freezing fresh food quickly to the core.
- Increasing the cold reserves in the stored goods before defrosting the appliance.

Activating/deactivating the function

- With a small amount to freeze:
- Activate 6 hours before use.
- With a maximum amount to freeze:
- Activate 24 hours before use.
- Activating/deactivating (see 6.2 Control concept). -or-

Activate/deactivate using the SmartDevice app.*

The function automatically turns off. The appliance goes back to normal mode. The temperature adjusts itself to the set level.

PartyMode

This option offers an assortment of special functions and settings that are useful if you are having a party.

The following functions are on:

- SuperCool
- SuperFrost
- IceMaker and MaxIce*

All the functions can be adjusted flexibly and separately. Changes are discarded when the function turns off.

Activating/deactivating the function

Activating/deactivating (see 6.2 Control concept).

 \triangleright On: All functions are activated at the same time.

▷ Deactivated: Previously set temperatures are restored. After 24 hours the function turns off automatically.

× HolidayMode

This function minimises the energy consumption during an extended absence. The temperature of the refrigerator compartment is set to 15 °C and this is displayed on the status screen when the temperature has been reached.

The set freezer temperature remains unchanged.

This function refers to the fridge section Fig. 1 (A).

Use:

- Save energy if you plan to be away for a while.
- Avoid coming home to bad smells and mould.

Activating/deactivating the function

- Empty everything from the fridge section.
- Activating/deactivating (see 6.2 Control concept).
- \triangleright On: Fridge temperature is raised.
- \triangleright Off: the previously set temperature is restored.

SabbathMode

With this function you can activate or deactivate the SabbathMode. If you activate this function, some electronic functions will be switched off. This allows your appliance to meet religious requirements on Jewish holidays such as the Sabbath and comply with STAR-K Kosher certification.

Appliance status with active SabbathMode

The status display continuously shows SabbathMode.

All functions in the display except the Deactivate SabbathMode function are locked.

Active functions remain active.

The display stays lit when you close the door.

The interior lighting is off.

Reminders are disabled. The set time intervals are paused.

Reminders and warnings are not displayed.

There is no door alarm.

There is no temperature alarm.

The IceMaker is out of operation.*

The defrost cycle only works for the specified time without taking account of appliance use.

After a power failure, the appliance returns to SabbathMode.

Appliance status

Note

This appliance has certification from the "Institute for Science and Halacha". (www.machonhalacha.co.il)

You can find a list of STAR-K-certified appliances at www.star-k.org/appliances.

Activating SabbathMode

WARNING

Danger of food poisoning from spoiled food!

If you have SabbathMode activated and a power failure occurs, no message appears in the status display about the power failure. Once the power is restored, the appliance continues to operate in SabbathMode. The power failure may mean that food spoils and the consumption of this food could lead to food poisoning. After a power failure:

▶ Do not consume food that was frozen and has thawed out.

- Call up the settings menu. (see 6.2 Control concept)
- Swipe left or right until corresponding function is displayed.



Fig. 12

- Complete the steps (see Fig. 987).
- ▷ SabbathMode is activated.
- ▷ Status display continuously shows SabbathMode.

Deactivating SabbathMode

- Call up the settings menu. (see 6.2 Control concept)
- ► Swipe left or right until corresponding function is displayed.



Fig. 13

- Complete the steps (see Fig. 988).
- ▷ SabbathMode is deactivated.



EnergySaver

This function activates or deactivates the energy-saving mode. When you activate this function, the energy consumption decreases and the temperature increases by 2 °C in the appliance. The food remains fresh, but the shelf life is shortened.

Temperature zone	Recom- mended setting	Temperature when Ener- gySaver activated
5 ° Fridge compart-	5 °C	7 °C
-18₀ Freezer compart- ment	-18 °C	-16 °C

Temperatures

Activating EnergySaver

Swipe left or right until corresponding function is displayed.



Fig. 14

- Complete the steps (see Fig. 989).
- \triangleright Energy-saving mode is activated.

Deactivating EnergySaver

Swipe left or right until corresponding function is displayed.



Fig. 15

- Complete the steps (see Fig. 990).
- ▷ Energy-saving mode is deactivated.

IceMaker / MaxIce*

You can activate or deactivate ice cube production with the IceMaker function. Use the MaxIce function to increase the number of ice cubes in the IceMaker.

More information on the number of ice cubes:	(see 9.1 Technical specifications)	
More information on the size of the ice cubes:	f (see Ice cubes*)	
More information on cleaning the lines of the IceMaker:	(see TubeClean*)	

Activating IceMaker

Make sure that the following requirements are fulfilled:

- □ The water supply is established at the fixed water connection. See installation instructions.
- IceMaker is put into operation. (see 7.10 IceMaker*)
- Swipe left or right until corresponding function is displayed.




Fig. 16

Complete the steps (see Fig. 991).

-or-

- Activate with the SmartDevice app.
- ▷ IceMaker is activated. It can take up to 24 hours for the IceMaker to produce the first ice cubes.

Activating the IceMaker with MaxIce

If you have not activated the IceMaker function before, make sure that the following requirements are met:

- The water supply is established at the fixed water connection. See installation instructions.
- IceMaker is put into operation. (see 7.10 IceMaker*)

 Swipe left or right until corresponding function is displayed.




Fig. 17

- Complete the steps (see Fig. 992) .
- Activate with the SmartDevice app.
- ▷ The IceMaker is activated with MaxIce.

Changing between the IceMaker and MaxIce

- If you have activated the IceMaker and would like to change to MaxIce:
- Swipe left or right until corresponding function is displayed.




Fig. 18

- Complete the steps (see Fig. 993) .
- \triangleright The IceMaker is activated with MaxIce.

If you have activated MaxIce and would like to change to the IceMaker:

Swipe left or right until corresponding function is displayed.




Fig. 19

- Complete the steps (see Fig. 994) .
- ▷ IceMaker is activated.
 ▷ MaxIce is deactivated.

Deactivating the IceMaker / MaxIce

Swipe left or right until corresponding function is displayed.




Fig. 20 Example illustration of the active IceMaker function
Complete the steps (see Fig. 995).

-or-

- Deactivate with the SmartDevice app.
- ▷ IceMaker and MaxIce are deactivated.
- \triangleright If ice cubes are currently being made, the system completes the process.
- > The iceMaker goes off automatically.



Set the ice cube size.*

Choose the setting*

Set the size in the Customer menu (see 6.2 Control concept).

TubeClean*

This setting cleans the IceMaker pipes.*

Ensure that the following conditions are met:*

□ IceMaker cleaning is ready (see 8.4.5 Cleaning the IceMaker*).

Activating the setting*

- Activate the setting in the Customer menu (see 6.2 Control concept).
- ▷ The rinse process is ready (max. 60 min.): Symbol flashes.
- \triangleright Water pipes are rinsed: Symbol flashes.
- Rinsing process is complete: Function turns off automatically.

CleaningMode

Use this setting to easily clean the appliance. This setting refers to the fridge section *Fig. 1 (A)*.

Use:

- Clean the fridge section by hand.
- What happens on the appliance when this setting is on:
- The display permanently shows: CleaningMode.
- The fridge section is switched off.
- The internal light is on.
- Reminders and warnings are not shown. There is no acoustic signal.

Activating/deactivating settings

- Activating/deactivating the setting (see 6.2 Control concept).
- \triangleright On: fridge section is off. Light stays on.
- \triangleright Off: preset temperature is restored.

After 60 min the setting turns off automatically. The appliance then continues running in normal mode.

Display brightness

Set the brightness level of the display.

You can set the following brightness levels:

- 40%
- 60%
- 80%
- 100%

Choose the setting

Set the level (see 6.2 Control concept) .



Door alarm

Set the time before the door alarm (see Close the door) sounds.

The options are as follows:

- 1 min
- 2 min
- 3 min
- Off

Choose the setting

▶ Set the time (see 6.4 Fault messages) .

Entry lock

This setting prevents unintentional use of the appliance, e.g. by children.

Use:

- Avoid settings being changed unintentionally.
- Avoid the appliance being switched off unintentionally.
- Avoid the temperature being changed unintentionally.

Activating/deactivating settings

Activating/deactivating. (see 6.2 Control concept)





This setting lets you choose the language of the display.

Choose from the following languages:

- German
- English
- French
- Spanish
- Italian
- Dutch
- Czech
- Polish
- Portuguese
- Russian
- Chinese

Activating/deactivating settings

Activating/deactivating (see 6.2 Control concept).



This setting allows the appliance information to be read out as well as access to the customer menu.

It provides the following information:

- Model name
- Index
- Serial number
- Service number

Show appliance data

- Swipe in the display until Settings 2 appears.
- Confirm the display.
- Swipe in the display until About appears.
- ▶ Read the appliance info.

ر ج Reminder

Reminders are given out acoustically by a beep and visually by a symbol in the display. The signal gets louder until the alert stops.

Replace FreshAir active carbon filter

This message appears when the air filter needs replacing.

- ► Change the air filter every six months.
- Confirm the message with OK.
- \triangleright The service interval resets.
- \triangleright The air filter guarantees the air quality in the fridge.

Activating the setting

Activating/deactivating (see 6.2 Control concept).

C Reset

This function resets all settings to the factory settings. All settings that you have made thus far will be reset to their original values.

Activating the setting

Activate (see 6.2 Control concept).

6.4 Fault messages

Fault messages appear in the display. There are two categories of fault message:

Category	Meaning
Message	Reminder of general procedures. You can carry out these procedures to eliminate the message.
Warning	Appears when there are malfunctions. A signal sounds in addition to the display. The signal becomes louder until you acknowledge by tapping the display. You can eliminate simple defects yourself. For more serious defects, you must contact customer service.

6.4.1 Warnings

Close the door

This message appears if the door is open for too long.

You can set how long it takes for this message to appear . ▶ Stop alarm: Confirm the message.

-or-



Power cut

This message appears if the freezer temperature increased due to a power cut. After the power is restored, the appliance continues to work at the set temperature.

- Stop alarm: Confirm the message.
- \triangleright Temperature alert appears (see Temperature alarm).



Temperature alarm

This message appears if the freezer temperature does not match the set temperature.

Variations in temperature could be because:

- Hot, fresh food was inserted.
- Too much warm room air flowed in when rearranging and removing food.
- The power was cut off for a while.
- The appliance is faulty.

When the fault is eliminated the appliance continues to work at the set temperature.

- Confirm the display.
- \triangleright The highest temperature is shown.
- Confirm display again.
- \triangleright The status display is displayed.
- \triangleright The current temperature is shown.

\bigotimes	Error

This message appears if there is a fault with the appliance. An appliance component indicates a fault.

- Open the door.
- ▶ Note down the fault code.
- Confirm the message.
- \triangleright The signal tone stops.
- \triangleright The status display appears.
- Close the door.
- Contact customer service. (see 9.4 Customer Services)

6.4.2 Message

Insert IceMaker drawer*

This message appears if the IceMaker drawer is open.

- Push in the IceMaker drawer.
- \triangleright The message disappears.
- \triangleright The IceMaker produces ice cubes.

6.4.3 DemoMode

If "D" appears on the display, demo mode is on. This option is designed for retailers, as it turns off all the cooling functions.

Stopping DemoMode

- If you see the following running in the display:
- Confirm the display within the countdown.
- \triangleright DemoMode is off.
- If the timer is not running:
- Unplug the appliance.
- Plug the appliance in again.
- \triangleright DemoMode is off.

7 Features

7.1 Door rack

7.1.1 Move/remove the door rack




Fig. 21

- Slide the rack upwards.
- Pull forwards.
- Re-insert it in reverse order.




Fig. 22

You can use just one or both VarioBoxes. To store oversized bottles, just suspend one box over the bottle rack.

Move the VarioBox shelf:




Fig. 23

- Pull it up and out.
- Put it back in at any position.

Moving the VarioBoxes:





Fig. 24

- If the door rack is removed:
- Remove containers.



Place the shelf on the table.




Fig. 26

- Pull off the middle holder *Fig. 26 (1)*.
- ▶ Insert the middle holder in the second position *Fig. 26 (2)*.




Fig. 27

Replace containers.

7.1.2 Disassembling the door rack

The door rack can be taken apart for cleaning.




Fig. 28




Fig. 29

▶ Disassemble the door rack.

7.2 Shelves

7.2.1 Adjusting/removing the shelves

The shelves are prevented from being pulled out accidentally by pull out stops.




Fig. 30

- Lift the shelf and pull forward.
- \triangleright Line up the side runner.
- ► Adjust the height of the shelf: Lift or lower it to the desired height and slide it in.

-or-




Fig. 31

- Remove the shelf completely: Pull it out to the front.
- Easier removal: Set the shelf at an angle.
- Insert the shelf again: Slide it in all the way.
- The pull-out stoppers point downwards.
- > The pull-out stoppers are behind the front support.

You can also remove the shelf above the EasyFresh compartments.




Fig. 32

Removing the shelf:


Pull it out towards you.

Do not store any goods on the compartment cover below! Inserting the shelf:

- Place the shelf at an angle, sloping down towards the back.
- \triangleright The pull-out stoppers point downwards.
- Slide the shelf into place.

7.2.2 Dismantling the shelves

The shelves can be dismantled for cleaning.



```
Fig. 33
```

Dismantling the shelf.

7.3 Dividing shelf

7.3.1 Using the dividing shelf

The shelves are prevented from being pulled out accidentally by pull out stops.




Fig. 34

▶ Push the dividing shelf underneath as shown.




Fig. 35

Adjusting the height:

- Pull the glass panels out Fig. 35 (1) from the front, one at a time.
- Release the support rails and click in at the height you want.
- Slide in the glass panels one at a time.
- Flat pull-out stoppers at the front, right behind the support rails.
- ▷ High pull-out stoppers at the back.

Using both shelves:

- Hold the glass panel with one hand and pull it to the front.
- ▷ The glass panel *Fig. 35 (1)* and trim strip are at the front.
- ▷ The stops *Fig. 35 (3)* point down.

7.4 VarioSafe

The VarioSafe provides space for compact foodstuffs and packages, pots and glasses.

7.4.1 Using the VarioSafe

You can remove the drawer and slide it back in at 2 different heights. This is handy for storing taller items in the drawer.




Fig. 36

- Remove the drawer.
- Slide back at the height you want Fig. 36 (1) or Fig. 36 (2).

7.4.2 Repositioning the VarioSafe

You can shift the height of the entire VarioSafe.




Fig. 37

- Pull forwards.
- \triangleright Line up the side runner.
- Lift or lower to the height you want.
- Slide to the rear.

7.4.3 Removing the entire VarioSafe

You can remove VarioSafe as a whole unit.

- ▶ Pull forwards.
- \triangleright Line up the side runner.





Fig. 38

► Tip to the side and pull towards you.

7.4.4 Disassembling the VarioSafe

You can take the VarioSafe apart for cleaning.



- Fig. 39
- Disassembling the VarioSafe

7.5 Space for baking tray

There is space for a baking tray *Fig. 1 (7)* above the drawers.



Fig. 40

Ensure that the following conditions are met:

- Max. baking tray dimensions are adhered to (see 9.1 Technical specifications).
- Baking tray is cooled to room temperature.
- $\hfill\square$ The lowest door rack is set at least one position higher.
- With the door open to 90°:
 Slide the baking tray onto the lower side runners.

7.6 Drawers

You can remove the drawers for cleaning.

You can remove the drawers to use VarioSpace.

The way to remove/insert the drawers varies depending on the pull-out system. Your appliance can contain various pull-out systems.

Note

The energy consumption increases and the cooling power goes down if ventilation is not sufficient.


- ► Leave the bottom drawer in the appliance!
- Always leave the fan air vents clear on the back wall!

7.6.1 Drawer on appliance base or glass shelf

The drawer runs directly on the appliance base or on a glass shelf. There are no rails.

When you remove the drawers, you can use the glass shelves below them as storage shelves.

Removing drawer



Fia. 41

▶ Remove drawer as shown in the illustration.

Inserting drawer




Fig. 42

▶ Insert drawer as shown in the illustration.

7.6.2 Drawer on telescopic rails

The drawer runs on extendible rails (telescopic rails). There are fully extendible telescopic rails and telescopic rails with partial pull-out. Drawers which are fully extendible can be pulled out fully from the appliance. Drawers with partial pull-out cannot be removed fully from the appliance. The system in your appliance depends on the type of appliance.

Fully extendible*

If you have fully extendible rails, there is a clamp located at the back on the left and right of the rail.

Removing drawer




Fig. 43

- Pull out drawer as far as it will go.
- Lift left clamp and simultaneously pull drawer forwards on the left. Fig. 43 (1)
 - Lift right clamp and simultaneously pull drawer forwards on the right. *Fig. 43 (2)*
- Remove drawer to the front. *Fig. 43 (3)*
- Slide rails in.

Inserting drawer




Fig. 44

- Slide rails in.
- Place drawer on rails.
- Slide in drawer to the back.
- ▷ Drawer latches in audibly at the back.

Partial pull-out fridge compartment*

Removing drawer




Fig. 45

- ▶ Pull out drawer half-way. *Fig. 45 (1)*
- Lift the drawer from the bottom. Fig. 45 (2)
- ▶ Lift and hold the drawer and at the same time pull it forwards.
- Insert left rail. Fig. 45 (3)
- Insert right rail. Fig. 45 (4)
- Remove drawer to the front. *Fig. 45 (5)*





Fig. 46

If the rails are not yet fully inserted after removing the drawer:

Push rails in completely.

Inserting drawer




- Fig. 47
- Slide rails in.
- Place drawer on rails.
- Slide in drawer to the back.

Partial pull-out freezer compartment

Note

- If the magnet on the top drawer in the freezer compartment
- is damaged or removed, the door sensors will malfunction.
- Do not damage or remove the magnet.

Removing drawer



- Fig. 48
- If the drawer is in the top freezer:
- Pull out drawer as far as it will go.
- Lift up drawer at the front. *Fig.* 48 (1)
- Remove drawer to the front. Fig. 48 (2)
- Slide rails in.




Fig. 49

If the drawer is in the middle part of the freezer compartment:

- Pull out drawer half-way.
- ▶ Lift drawer from below. *Fig. 49 (1)*
- Remove drawer to the front. Fig. 49 (2)
- Slide rails in.

Features

Inserting drawer




Fig. 50

- Slide rails in.
- Guide drawer around the stoppers *Fig. 50 (1)*.
- Place drawer on rails.
- Slide in drawer to the back.

7.7 EasyFresh-Safe cover

You can remove the compartment cover for cleaning.

7.7.1 Removing the compartment cover




Fig. 51

When the drawers are removed:

- Pull the lid up at the front to the opening in the retaining parts Fig. 51 (1).
- Lift from the back and pull it up and out *Fig. 51 (2)*.

7.7.2 Inserting the compartment cover




Fig. 52

- If the text THIS SIDE UP points upwards:
- Insert the lip of the cover over the opening of the rear bracket Fig. 52 (1) and click into place Fig. 52 (2).
- Position the cover where you want it (see 7.8 Adjusting the moisture levels).

7.8 Adjusting the moisture levels

You can adjust the moisture in the drawer yourself by adjusting the compartment cover.

The compartment lid is attached to the drawer and can be hidden by a shelf or additional drawers.




Fig. 53

- Low air humidity
- ▶ Open the drawer.
- ▶ Slide the compartment cover forwards.
- ▷ With the drawer closed: Gap between the cover and the compartment.
- \triangleright The air moisture in the Safe decreases.

High air moisture

- Open the drawer.
- Slide the cover back.
- With the drawer closed: The cover seals the compartment.
- \triangleright The air moisture in the Safe increases.
- If there is too much moisture in the compartment:
- Choose the setting "low air moisture".
- -or-
- Remove any excess moisture with a cloth.

7.9 Glass shelves

You can remove the glass shelves under the drawers for cleaning.

You can remove the glass shelves under the drawers to use VarioSpace.

7.9.1 Removing / inserting the glass shelf

Make sure that the following requirements are fulfilled:

□ Glass shelf under the drawer: The drawer has been removed. (see 7.6 Drawers)

Removing glass shelf




Fig. 54 Example illustration of glass shelf

- ▶ Lift glass shelf at the front. *Fig.* 54 (1)
- ► Take out glass shelf to the front. *Fig. 54 (2)*

Inserting glass shelf




Fig. 55 Example illustration of glass shelf

- Position glass shelf at an angle behind the stoppers. (see Fig. 1030)
- ► Lower glass shelf.
- Slide in glass shelf to the back.

7.10 IceMaker*

The IceMaker will produce ice cubes for household use only.

Ensure that the following conditions are met:

- IceMaker is cleaned (see 8 Maintenance) .
- IceMaker drawer is cleaned.
- IceMaker drawer is fully inserted.

7.10.1 Producing ice cubes

The volume depends on the freezing temperature. The colder the temperature, the more ice cubes the system can produce in a certain time period.

After the IceMaker is turned on for the first time, it can take up to 24 hours for the first ice cubes to be made.

- Activate the IceMaker function (see 6.2 Control concept).
- To make a high number of ice cubes: Activate the MaxIce function (see 6.2 Control concept).
- ► To make a high number of ice cubes: Move the divider in the IceMaker drawer or remove it completely.*
- Distribute the ice cubes evenly in the drawer to increase the capacity.
- Closing the drawer: IceMaker starts making ice cubes again automatically.

Note

When a certain level is reached in the IceMaker drawer, it stops producing ice cubes. The IceMaker does not fill the drawer all the way to the top.

7.10.2 Using the drawer with the IceMaker deactivated

If you deactivate the IceMaker, then you can use the entire IceMaker drawer as a freezer drawer.

 Deactivate IceMaker. (see 6.3.12.4 Deactivating the IceMaker / MaxIce)




Fig. 56

- Place food in drawer.
- If you put food in the left side of the drawer:
- ▶ Watch out for the IceMaker *Fig. 56 (1)*.

7.11 VarioSpace




Fig. 57


You can remove drawers and glass panels from your appliance. This provides more room for large food items such as poultry, joints of meat, large game, and tall baked products. You can then freeze these items whole for later preparation.

Note the weight limits on the drawers and glass panels (see 9.1 Technical specifications).

7.12 Accessories

7.12.1 Butter dish


Opening/closing the butter dish





Dismantling the butter dish

You can take the butter dish apart for cleaning.





Features

► Disassembling the butter dish.

7.12.2 Egg rack

You can pull out and turn the egg rack. You can use both sides of the egg rack so you can label specifics like the purchase date.

Using the egg rack




Fig. 60

- Top layer: for storing hen eggs.
- Bottom layer: for storing quail eggs.

7.12.3 Bottle holder

Using the bottle holder




Fig. 61

- Push the bottle holder onto the bottles.
- \triangleright The bottles are prevented from falling over.

Removing the bottle holder




Fig. 62

• Move the bottle holder all the way to the right.

Push the bottle holder to the back to remove.

7.12.4 Freezer pack

Freezer packs prevent the temperature rising too quickly should there be a power cut.

The freezer packs are in the drawer.

You can store the freezer packs in the freezer tray.*

Using the freezer pack

Fig. 63

When the freezer packs are fully frozen:

Place on the frozen goods in the top, front part of the freezer.

7.12.5 Ice cube tray with cover*

Using the ice cube tray




Fig. 64

When the water is frozen:

- Hold ice cube tray under hot water for a short time.
- Remove the lid.
- Gently turn the ends of the ice cube tray in opposite directions.
- Release the ice cubes.

Dismantling the ice cube tray

You can take the ice cube tray apart for cleaning.




Fig. 65

Disassembling the ice cube tray.

7.12.6 Flexible ice compartment divider*

The IceMaker's ice cube drawer has a flexible ice compartment divider. This allows you to store larger quantities of ice cubes or additional food items as needed. You can move or remove the ice compartment divider.

Moving in the flexible ice compartment divider




Fig. 66 Example illustration of the ice compartment divider
Move the ice compartment divider to the desired position.

Removing the flexible ice compartment divider

Make sure that the following requirements are fulfilled: Ice cube drawer is removed. (see 7.6 Drawers)




Fig. 67

- ▶ Lift the rear part of the ice compartment divider. Fig. 67 (1)
- Remove the ice compartment divider upwards. *Fig. 67 (2)*

Putting in the flexible ice compartment divider

Make sure that the following requirements are fulfilled: Ice cube drawer is removed. (see 7.6 Drawers)




Fig. 68

- Insert the front part of the ice compartment divider. Fig. 68 (1)
- Lower the rear part of the ice compartment divider to the drawer bottom. Fig. 68 (2)

8 Maintenance

8.1 FreshAir carbon filter

The FreshAir carbon filter is in the compartment above the fan.

It guarantees the best air quality.

 $\hfill\square$ Replace the carbon filter every 6 months.

When the reminder is set, a message on the display prompts you to change it.

The carbon filter can be disposed of with the regular household waste.

Note

FreshAir activated charcoal filters can be purchased from the Liebherr-Hausgeräte store at home.liebherr.com/ shop/de/deu/zubehor.html.

8.1.1 Removing the FreshAir carbon filter




Fig. 69

- ▶ Pull out the compartment *Fig. 69 (1)*.
- Remove the carbon filter *Fig. 69 (2)*.

8.1.2 Inserting the FreshAir carbon filter




Fig. 70

- ▶ Insert the carbon filter as shown in the diagram *Fig. 70 (1).*
- ▷ The carbon filter clicks into place.
- If the carbon filter is pointing downwards:
- Push the compartment in *Fig. 70 (2)*.
- \triangleright The carbon filter is now ready for use.

8.2 Disassembling / assembling pullout systems

8.2.1 Notes on disassembly

You can disassemble some of the pull-out systems for cleaning. Your appliance can contain a variety of pull-out systems.

The following pull-out systems can be disassembled or cannot be disassembled:

Pull-out system	can be disassembled / cannot be disassembled
Drawer on appliance base or glass shelf	cannot be disassembled
Fully extendible*	cannot be disassembled*

Maintenance

Pull-out system	can be disassembled / cannot be disassembled	
Partial pull-out fridge compartment*	cannot be disassembled*	
Partial pull-out freezer compartment	can be disassembled (see 8.2.2.1 Partial pull-out freeze compartment)	

8.2.2 Drawer on telescopic rails

Partial pull-out freezer compartment

Disassembling pull-out system

- Make sure the following prerequisites are met:
- Drawer has been removed.
- Glass shelf has been removed. (see 7.9 Glass shelves)




Fig. 71 Glass shelf with rails

- Push up front click-in hooks. Fig. 71 (1)
- Move the pull-out rails to the side Fig. 71 (2) and to the rear Fig. 71 (3).

Installing pull-out system




Fig. 72 Glass shelf with rails

- Hook in rail at the back. Fig. 72 (1)
- Hook in rail at the front. Fig. 72 (2)

8.3 Defrosting the appliance

8.3.1 Defrosting the fridge compartment

Defrosting is performed automatically. The water from the thawing process drains through the outlet and evaporates.

Clean the drain opening regularly (see 8.4 Cleaning the appliance).

8.3.2 Defrosting the freezer compartment with NoFrost

Defrosting is performed automatically with the NoFrost system. The moisture is deposited on the evaporator, is periodically defrosted and evaporates.

The appliance does not need to be defrosted.

8.4 Cleaning the appliance

8.4.1 Ready



WARNING

Danger of electric shock!

Remove the refrigerator connector or interrupt the power supply.

WARNING

Risk of fire

Do not damage the refrigeration circuit.

- Empty the appliance.
- Remove mains connector.
- -or-
- Activate CleaningMode. (see CleaningMode)

8.4.2 Cleaning the interior

NOTICE

Improper cleaning!

Damage to the appliance.

- Only use soft cleaning cloths and ph-neutral all-purpose cleaners.
- Do not uses abrasive sponges or steel wool which may cause scratches.
- Do not use any sharp or abrasive cleaning agents, nor any that contain sand, chloride or acid.
- Plastic surfaces: clean by hand with a soft clean cloth, lukewarm water and a little detergent.
- Metal surfaces: clean by hand with a soft clean cloth, lukewarm water and a little detergent.
- Drain hole: remove deposits using a thin item (for example a cotton bud).

8.4.3 Cleaning the dry rear panel

You can remove the dry rear panel for cleaning.

Removing the rear panel

Remove all equipment parts.




Fig. 73

- Hold the rear panel with both hands at the bottom and pull downward vigorously at the same time.
- Pull the rear panel out to the front by the bottom end. \triangleright The rear panel has been removed.
- If you want to continue operating the appliance with the rear panel removed:
- Set the D-Value to D2. (see D-Value)

Inserting the rear panel



Fig. 74

- Make sure the appliance is completely empty.
- Slide in the rear panel from below to the top.
- Press back vigorously on the left-hand side of the rear panel.
- \triangleright The rear panel clicks into place.
- Insert the equipment parts.
- Set the *D-Value* to *D1*. (see D-Value)

8.4.4 Clean the components

NOTICE

Improper cleaning!

- Damage to the appliance.
- Only use soft cleaning cloths and ph-neutral all-purpose cleaners.
 Do not uses abrasive sponges or steel wool which may
- Do not use any sharp or abrasive cleaning agents, nor
- Do not use any sharp or abrasive cleaning agents, nor any that contain sand, chloride or acid.

Clean with a soft, clean cloth, lukewarm water and some detergent:

- VarioSafe

- EasyFresh-Safe cover
- Drawer
- Please note: Do not remove the magnet on the drawer. The magnet ensures the functionality of the IceMaker.*
- Divider in the IceMaker drawer*
- Freezer tray*

Clean with a damp cloth:

- Retractable rails
 - Please note: The grease in the tracks is used for lubrication and must not be removed!

Wash in the dishwasher up to 60 °C:

- Door rack
- VarioBox
- Bottle rack
- Shelf
- Dividing shelfHolder of the dividing shelf
- Holder of the
 Egg rack
- Egg rack
 Butter dish
- Ice cube tray*
- Ice cube scoop*
- ► To disassemble components: see the relevant section.
- Clean the components.

8.4.5 Cleaning the IceMaker*

There are various options for cleaning the IceMaker.

- Cleaning is required in the following cases:
- Initial operation
- □ If out of use for more than 5 days.

Ensure that the following conditions are met: IceMaker drawer is emptied.

IceMaker drawer is in place.

□ The IceMaker is activated. (see 6.2 Control concept)

First use or after a long period of non-use

Clean the IceMaker with the TubeClean function.

- Place a 1.5 l empty container (max. height 10 cm) into the drawer under the IceMaker.
- Activate the TubeClean function. (see 6.2 Control concept)
- The rinse process is prepared (max. 60 min.): Symbol flashes.
- ▷ Water pipes are rinsed: Symbol flashes.
- Rinsing process is complete: Function turns off automatically.
- Remove the IceMaker drawer and remove the container.
- Clean the IceMaker drawer with warm water and a little detergent.
- Push the IceMaker drawer in.
- \triangleright The system starts making ice cubes automatically.
- Dispose of any ice cubes that were made 24 hours after the first ice cubes.

If cleaning is required

Clean the IceMaker by hand.

- Remove the IceMaker drawer and clean with warm water and a little detergent.
- Push the IceMaker drawer in.
- \triangleright The system starts making ice cubes automatically.

8.4.6 After cleaning

- ▶ Wipe the appliance and the components dry.
- Connect and switch on the appliance.
- Activate SuperFrost (see 6.3 Functions).
- The temperature is cold enough: Place the food inside
 - Place the food inside.
 Popost closping regular.
- Repeat cleaning regularly.

9 Customer help

9.1 Technical specifications

Temperature range			
Cooling		2 °C to 9 °C	
Freeze		-26 °C to -15 °C	
Maximum freezing quantity / 24 h			
Freezer ment	compart-	See "Freezing capacity /24 h" on the serial tag	

Maximum component capacity

Appliance width 550 mm (see instal- lation instruc- tions, appliance dimen- sions)	Appliance width 600 mm (see installa- tion instruc- tions, appliance dimen- sions)	Appliance width 700 mm (see instal- lation instruc- tions, appli- ance dimen- sions)	
12 kg	15 kg		
	Appliance width 550 mm (see instal- lation instruc- tions, appliance dimen- sions)	Appliance widthAppliance width550mm600(see instal- lation instruc- tions, appliance dimen- sions)(see installa- tions instruc- tions, appliance dimen- sions)	

Maximum component capacity				
Features	Appliance width 550 mm (see instal- lation instruc- tions, appliance dimen- sions)	Appliance width 600 mm (see installa- tion instruc- tions, appliance dimen- sions)	Appliance width 700 mm (see instal- lation instruc- tions, appli- ance dimen- sions)	
Partial pull-out freezer compart- ment	12 kg	15 kg		
(see 7.6.2 Drawer on telescopic rails)				
Maximum size baking tray				
Width	466 mm			
Depth	386 mm			
Height	50 mm			
Ice cube production with IceMaker*				
Ice cube produc- tion / 24 h	At a temperature of -18 °C: 1.2 kg of ice cubes			
Maximum ice cube production / 24 hours	With the MaxIce function on: 1.5 kg of ice cubes			
Lighting				
Class ¹ Light source			Light source	
This product contains one or more energy LED efficiency class F light sources.				

1 The appliance may contain light sources with different energy efficiency classes. The lowest energy efficiency class is indicated.

For appliances with a WiFi connection:*

Frequency specification*		
Frequency band	2.4 GHz	
Maximum radiated power	< 100 mW	
	Integration in the local WiFi network for data communication	

9.2 Operating noises

The appliance makes different noises when it is on.

- At higher temperatures the appliance uses less energy but works for longer. It is quieter.
- At lower temperatures the food is cooled faster. It is louder.

Examples:

- Functions on (see 6.3 Functions)
- Fan running
- Food recently added
- High ambient temperature
- Door open for a while

Noise		Possible cause		Type of noise	
Bubbling splashing	and	Coolant into the circuit.	flowing cooling		operating
Hissing		Coolant into the circuit.	sprays cooling		operating
Humming			appliance ng. The depends cooling		operating
Suction noises		Soft-closir is being and closed	opened		operating
Humming rustling	and	The fan is	running.	Normal noise	operating
Clicking		Componer switched off.			switching
Rattling humming	or	Valves or working.	flaps are	Normal noise	switching
Noice	Deer	aible	Tung of p		in a

Noise	Possible cause	Type of noise	Lifting
Vibration	Improper installation	Defective noise	Check the installation.
			Level the appliance.
Rattling	Components, items inside	Defective noise	Secure components.
	the appliance		Leave enough space between the items.

9.3 Technical fault

Your appliance is designed and built to ensure it works reliably and has a long service life. In the unlikely event that a fault occurs during operation, please check whether it is due to an operating error. If so, you will be charged for the callout and repair costs even if it falls within the warranty period.

You can fix the following faults yourself.

9.3.1 Appliance function

Defect	Cause	Remedy	
The appliance is	\rightarrow The appliance is not switched on.	 Switch the appliance on. 	
not working.	→ The power plug is not properly plugged into the socket.	 Check the power plug. 	

Defect	Cause	Remedy
	→ There is something wrong with the power outlet fuse.	 Check the fuse.
	→ Power cut	 Keep the appliance closed. Protecting food: Lay freezer packs on top of the food or use another freezer if the power is off for a prolonged period. Do not re-freeze defrosted food,
	→ The appliance plug does not fit the appliance properly.	 Check the appliance plug.
Temperature is not cold enough.	→ The appliance door is not closed properly.	 Close the appliance door.
	\rightarrow Not enough ventilation.	 Keep ventilation grille clear, and clean it.
	→ The ambient temperature is too high.	 Solution: (see 1.4 Appliance range of use).
	→ The appliance was opened too many times or for too long.	 Wait to see if the required temperature corrects itself. If not, contact Customer Service (see 9.4 Customer Serv- ices).
	→ Too much fresh food was placed inside without SuperFrost.	 Solution: (see SuperFrost)
	ightarrow The temperature is set incorrectly.	Turn down the temperature and check after 24 hours.
	→ The appliance is too close to a heat source (oven, radiator, etc).	Move the appliance or the heat source.
	→ The appliance was not correctly installed in the recess.	Check if the appliance was installed correctly and that the door closes properly.
The door seal is defective or needs to be replaced for another reason.	→ The door seal can be replaced. It can be replaced without the need for special tools.	 Contact Customer Services (see 9.4 Customer Services).
The appliance builds up too much ice or condensa- tion.	→ The door seal may have slipped out of its groove.	 Check that the door seal is well fitted in the groove.

9.3.2 Features

Defect	Cause	Remedy
You cannot acti- vate the IceMaker.*	→ The appliance and therefore the IceMaker are not connected.	 Connect the appliance (see the Installation Guide).
The IceMaker is	→ The IceMaker is not on.	 Activate the IceMaker.
not producing ice cubes.*	→ The drawer of the IceMakers is not connected properly.	Push the drawer in correctly.
	→ The water connection is not open.	 Open the water connection.
The internal light	ightarrow The appliance is not switched on.	 Switch the appliance on.
does not come on.	→ The door was open for longer than 15 minutes.	 Interior lighting turns off automatically after approx. 15 min. with the door open.
	→ The LED interior light is faulty or the lid is damaged.	 Contact customer service (see 9.4 Customer Services).

9.4 Customer Services

First check if you can fix the error yourself (see 9 Customer help) . If you can't, contact Customer Services.

Please refer to the enclosed "Liebherr-Service" brochure for the address.

Unprofessional repair! Injuries.

- Have any repairs and action not expressly specified on the appliance and mains cable carried out by service personnel only. (see 8 Maintenance)
- A damaged mains cable may only be replaced by the manufacturer, the manufacturer's Customer Service or a similarly qualified person.
- In the case of appliances with an IEC connector, the change may be made by the customer.

9.4.1 Contact Customer Services

Make sure you have the following appliance data at the ready:

Appliance name (model and index)

- Service no. (Service)
- 🗖 Serial no. (S no.)
- Look up the appliance information on the display (see Info).
 -or-
- Referring to appliance info on the nameplate (see 9.5 Model plate).
- ▶ Note down the appliance information.
- ▶ Notify Customer Services of the following: Give us the appliance data.
- ▷ This will help us to provide you with a faster, more accurate service.
- Follow any further instructions given by Customer Services.

9.5 Model plate

The model plate is behind the drawers on the inside of the appliance.




Fig. 75

(1) Appliance description(3) Serial no.(2) Service no.

▶ Note the data on the model plate.

10 Shutting down

- Empty the appliance.
- Turn off the IceMaker .*
- Turn off the appliance .
- Remove mains connector.
- Remove appliance connector if required: Remove and move from left to right at the same time.
- ► Clean the appliance (see 8.4 Cleaning the appliance).
- Leave the door open to avoid bad smells building up.

11 Disposal

11.1 Preparing appliance for disposal



Liebherr uses batteries in some of its appliances. In the EU, for environmental reasons, legislation obliges the end user to remove these batteries before disposing of old appliances. If your appliance contains batteries, a corresponding notice is attached.

Lamps If you can remove the lamps yourself without destroying them, also remove these before disposal.

- ► Take the appliance out of operation.
- Appliances with batteries: remove the batteries. For description, see Maintenance chapter.
- If possible: remove lamps without destroying them.

11.2 Disposing of the appliance in an environmentally friendly manner



The appliance still contains valuable materials and must be disposed of separately from unsorted municipal waste.



Dispose of batteries separately from the old appliance. To do this, you can return the batteries free of charge to retailers as well as recycling centres and collection centres for recyclable materials

Lamps

For Germany:

materials. Dispose of removed lamps via the respective collection systems.

You can dispose of the appliance free of charge via the class 1 collection containers at the local recycling and recyclable material collection centres. When purchasing a new fridge/freezer, if the sales area > 400 m², retailers will also take back the old appliance free of charge.



Leaking coolant and oil!

Fire. The coolant contained in the appliance is eco-friendly, but also flammable. The oil contained in the appliance is flammable. Escaping coolant and oil can ignite if the concentration is high enough and in contact with an external heat source.

- ▶ Do not damage the pipelines of the coolant circuit and the compressor.
- ▶ Transport the appliance without damaging it.
- Dispose of batteries, lamps and the appliance according to the above specifications.



home.liebherr.com/fridge-manuals

EN Integrated fridge/freezer

Part number index: 7088255-00

Liebherr-Hausgeräte GmbH Memminger Straße 77-79 88416 Ochsenhausen Deutschland

Issue date: 20230406