

LIEBHERR





2.4" Touchscreen Display: Located behind the appliance door, this high-resolution and high-contrast 2.4" touchscreen display can be read from any angle. Stored menu options are inituitive and easy-to-operate.



BioFresh: When stored at Biofresh's precisely maintained temperature of 0°C and correct humidity level, nutrients in your food are retained. Our BioFresh drawers fully extend on telescopic rails and feature a self-closing mechanism.




PowerCooling: A high-performance system that allows freshly stored items to be chilled rapidly while maintaining an even temperature throughout the interior. In this energy-efficient BluPerformance range, the fan switches off when the appliance door is opened, saving valuable energy.

Volume, efficiency, economy, ease of use, and outstanding design are the key features of the **SBSbs 8673** BlackSteel side-by-side fridge-freezer from Liebherr's BluPerformance series. High-quality components and materials, and perfect workmanship combined with precise touch electronics system are what made this appliance so efficient.


BioFresh technology allows your fruits, vegetables, meat, fish, and dairy products to stay fresher for longer. Meanwhile NoFrost technology ensures that this appliance never has to be defrosted. And thanks to its premium SmartSteel surface, this timelessly elegant model is easy to clean and will definitely be a visual highlight in your home!

Bio No Ice Soft Soft Smart

Premium	Fresh	Frost	Maker	System	Telescopic	Steel			
*Side-by-Sides comprised of two models				SGNPbs 4365				SKBbs 435	50
Energy consumption (kWh/yr) I Star rating				199 5.0				120 6	.0
Compressors				1					1
Total Usable Litres				277				37	73
Refrigerator Usable Litres				-				23	36
Freezer Usable Litres				277					-
BioFresh Usable Litres				-				10	37
Control system and display I Child proof				2.4"Touch display Yes				2.4"Touch display Y	es
PremiumPlus LED : lighting				- I Yes				Yes	۱ -
Sabbath mode				Yes				Y	es
SoftSystem hinge - assists closure				Yes				Y	es
Door open I Temperature : alarms				Yes I Yes				Yes	-
BioFresh drawers on telescopic rails				-					3
SuperCool VarioSafe				- -				Yes I Y	es
SuperFrost VarioSpace				Yes I Yes				-	-
Integrated bottle shelf				-				Y	es
Freezer drawers I Ice cube drawer				8 1				-	۱ -
IceMaker I Ice cube capacity (kg/24h)				Yes 0.8				-	-
Stainless steel hose	tainless steel hose supplied (m)			1.5					-
BlackSteel with SmartSteel Doors Walls				Yes I Yes				Yes I Y	es
Default hinge				Left				Rig	ht
• . ,	Voltage (V) Rated Current (A)			220 - 240 1.3				220 - 240 1	
Made in						Germ	nany	Germa	ny



1 To achieve the indicated energy consumption level, the wall spacers provided with the appliance must be used. This increases the appliance depth by approximately 1.5 cm. If the wall spacers are not used, the appliance will remain fully functional, but will have a slightly higher energy consumption level.



b = 700 mm c = 110 mm ivi = Soleriola valve

Plumbing must be installed adjacent to the side of the appliance which contains the IceMaker.

Water pressure must be between 0.15 MPa and 0.6 MPa (1.5 bar - 6 bar)

Important information: For Side-by-Side installation the freezer or the appliance with freezer compartment must be installed on the left as viewed from the front to prevent possible formation of condensation.

Note: Whilst every effort is made to ensure all specifications and information in this flyer are accurate, Liebherr reserves the right to make changes without notification. Where actual appliance measurements, specifications, and ratings are crucial, we recommend that the actual appliance installation instructions that accompany each appliance be checked. Liebherr will not be liable for any loss.

SBSbs 8673